| | RACOON 95 | RACOON 95-4X4 | RACOON 110-4X4 | RACOON 95-4X4 KOMMUNAL |
|---|---|---|---|---|
| **Engine** | | | | |
| **Model** | B&S 2 Cylinder Series 7-40T8 | B&S 2 Cylinder Series 8-44C8 | B&S 2 Cylinder Vanguard 49R9 | B&S 2 Cylinder Vanguard 49R9 |
| **Power** | 24HP | 25HP | 26HP | 26HP |
| **Displacement** | 656 ccm | 724 ccm | 810 ccm | 810 ccm |
| **Tank capacity** | 18 liters | 18 liters | 18 liters | 18 liters |
| **Oil capacity** | 1,9 liters | 1,9 liters | 2,0 liters | 2,0 liters |
| **Battery power** | 12V-28Ah | 12V-28Ah | 12V-28Ah | 12V-28Ah |
| **Air Filtering** | Cyclone Profifilter | Cyclone Profifilter | 5" Donaldson Airfilter | 5" Donaldson Airfilter |
| **Traction drive** | | | | |
| **Drive** | rear-wheel drive | all-wheel drive | all-wheel drive | all-wheel drive |
| **Lock** | 100 % switchable differential lock | 100 % switchable differential lock | 100 % switchable differential lock | 100 % switchable differential lock |
| **Travel speed** | 0-8 km/h forward/ 0-6 km/h backward | 0-8 km/h forward/ 0-6 km/h backward | 0-8 km/h forward/ 0-6 km/h backward | 0-8 km/h forward/ 0-6 km/h backward |
| **Driving actuation** | single pedal for vw/-rw driving | single pedal for Vw/-Rw driving | single pedal for Vw/-Rw driving | single pedal for Vw/-Rw driving |
| **Differential lock** | front pedal | front pedal | front pedal | front pedal |
| **Front wheels** | 16x6.50-8" AS Tyres | 16x6.50-8" AS Tyres ???? | 16x6.50-8" AS Tyres | 16x6.50-8" AS Tyres |
| **Rear wheels** | 20x10-8" AS Tyres | 18x9.50-8" AS Tyres ???? | 18x9.50-8" AS Tyres | 18x9.50-8" AS Tyres |
| **Steering system** | rack and pinion steering | rack and pinion steering | rack and pinion steering | rack and pinion steering |
| **Seat** | standard seat | standard seat | comfort seat | comfort seat |
| **Service brake** | additional front drum brake | via front all-wheel drive | via front all-wheel drive | via front all-wheel drive |
| **Parking brake** | brake pedal lock | brake pedal lock | brake pedal lock | brake pedal lock |
| **Mower housing** | | | | |
| **Flail shaft** | 95 cm, 52 Y flail knife | 95 cm, 52 Y flail knife | 110 cm, 60 Y flail knife | 95 cm, 26 hammer flail knife |
| **Drive** | V-belt can be engaged via a knife clutch | V-belt can be engaged via a knife clutch | V-belt can be engaged via a knife clutch | V-belt can be engaged via a knife clutch |
| **Knife stop** | automatic band brake on switch off | automatic band brake on switch off | automatic band brake on switch off | automatic band brake on switch off |
| **Protective device** | chains front, rubber tarpaulin rear | chains front, rubber tarpaulin rear | rubber tarpaulin front / rear | chains front, rubber tarpaulin rear |
| **Cutting height** | 30-90 mm, 4 fixed & 6 floating positions | 30-90 mm, 4 fixed & 6 floating positions | 30-90 mm, 4 fixed & 6 floating positions | 30-90 mm, 4 fixed & 6 floating positions |
| **Optional** | | | | |
| | hammer flail knife | hammer flail knife (26 pieces) | hammer flail knife (30 pieces) | hammer flail knife inklusive |
| | LED work lights | LED work lights | LED work lights | LED work lights inklusive |
| | LED rotating beacon | LED rotating beacon | LED rotating beacon | LED rotating beacon inklusive |
| | inclination adjustable seat on request | inclination adjustable seat on request | inclination adjustable seat on request | inclination adjustable seat on request |
| | foldable armrests | foldable armrests | foldable armrests | foldable armrests included |
| **Dimensions** | | | | |
| **Dimensions L x W x H** | 220 x 111 x 113 cm | 220 x 111 x 121 cm | 220 x 126 x 121 cm | 220 x 111 x 121 cm |
| **Center Distance** | 135 cm | 135 cm | 135 cm | 135 cm |
| **Weight** | 347,5 kg | 388 kg | 399 kg | 388 kg |
| **Lashing points** | each 2 x front/-rear | each 2 x front/-rear | each 2 x front/-rear | each 2 x front/-rear |
| **Crane eye** | 3 points (1x front/-2x rear) | 3 points (1x front/-2x rear) | 3 points (1x front/-2x rear) | 3 points (1x front/-2x rear) |

Stella engineered